



Hand-drawn architectural floor plan of a three-story building. The plan includes the following details:

- Top Floor (Pietro IV/V):** Labeled with a total area of  $+ 12,27m$ . It contains a large central room with a staircase and several smaller rooms. Dimensions for this floor include  $618-$ ,  $622-$ , and  $621-$ .
- Middle Floor (Pietro III/V):** Labeled with a total area of  $H_p = 154 cm$ . It contains a large central room with a staircase and several smaller rooms. Dimensions for this floor include  $618-$ ,  $622-$ , and  $621-$ .
- Bottom Floor (Pietro II/V):** Labeled with a total area of  $H_p = 154 cm$ . It contains a large central room with a staircase and several smaller rooms. Dimensions for this floor include  $618-$ ,  $622-$ , and  $621-$ .
- Overall Dimensions:** The building footprint is defined by a large rectangle with dimensions  $12,27m$  (width) and  $154 cm$  (height).
- Rooms and Features:** The plan shows various rooms, including bedrooms, bathrooms, and a central staircase area. Rooms are labeled with numbers such as 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100.

Zestawienie stolarki okiennej.	 <p>SYSTEM FASADOWY ALUMINIOWY, PROFILE ALUMINIOWE O KRAWĘDZICH PROSTYCH, LAKIEROWANE PROSZKOWO W KOLORZE STALOWO SZARYM WG RAL 9007 (OD WEWNĄTRZ KOLOR RAL 9005) SZKLENIE DWUKOMOROWE, ZESPOLONE, SZKLENIE ESG MLECZNE, NIEPRZEZIERNE, ATYWŁAMANIOWE, WSPÓŁCZYNNIK U DLA ZESTAWU MAX. 0,9 W/ M<sup>2</sup>, OKUCIA ZE STALI NIERDZEWNEJ.</p>	6	szt.
	 <p>SYSTEM FASADOWY ALUMINIOWY, PROFILE ALUMINIOWE O KRAWĘDZICH PROSTYCH, LAKIEROWANE PROSZKOWO W KOLORZE STALOWO SZARYM WG RAL 9007 (OD WEWNĄTRZ KOLOR RAL 9005) SZKLENIE DWUKOMOROWE, ZESPOLONE, SZKLENIE ESG MLECZNE, NIEPRZEZIERNE, ATYWŁAMANIOWE, WSPÓŁCZYNNIK U DLA ZESTAWU MAX. 0,9 W/ M<sup>2</sup>, OKUCIA ZE STALI NIERDZEWNEJ.</p>	36	
SUMA:			42